



NEW ITEMS

Bulletin

"Since 1916"



HNI-451 - 04/26/2019

For Bulletin Archive Navigate to:

www.auveco.com/hot-new-items

1-800-354-9816 ext.1

Fax: 1-800-552-8197

Connect with us



Items Available for Immediate Shipment



22723

(Ford: W706436-S300)
White Nylon

Tail Lamp Screw Grommet with Sealer
Screw Size: M4.8 (#10)
Head Diameter: 16mm
Stem Length: 27mm
Overall Height: 28.5mm
Fits into 8mm Square Hole
Ford Focus & Transit
2013 - On

UNIT PACKAGE: 25



22720

(VW: N105-073-01)
Brown Nylon

Bumper & Fender Apron
Screw Grommet with Sealer
Screw Size: M4.8 (#8)
Head Diameter: 13mm
Stem Length: 17mm
Fits into 7.5mm x 7.5mm Hole
Audi A3, A4, A5, RS 5, S4 & S5
2015 - 2009
Volkswagen Phaeton
2006 - 2004

UNIT PACKAGE: 25



22721

(VW & Porsche: N905-410-01)
Natural Nylon

Deck Lid & Hood Release Handle
Screw Grommet
Screw Size: M4.2 (#8)
Head Size: 9.5mm x 9.5mm
Stem Size: 8mm x 9mm
Stem Length: 7.5mm
Fits into 7.5mm Slot
Porsche Cayenne & Macan
2017 - 2003
Volkswagen Beetle, Golf,
Golf R, Jetta, Tiguan
2016 - 2010

UNIT PACKAGE: 50

SXL CROSS-LINKED POLYETHYLENE WIRE



- Abrasion-resistant design is resistant to moisture, oil, grease, gasoline, and other damaging solvents.
- Enhanced durability and self-extinguishing cross-linked polyethylene insulation.
- Works well in engine compartments where strict temperature ranges are required.
- Temperature rated at -40°C (-40°F) 125°C (257°F)
- Specifications: SAE J1128, Ford ESB-M1L 123A, and Chrysler MS-5919

Unit Package: 1 Spool (100 Foot Spool)

CALIFORNIA PROPOSITION 65 **Warning:** CANCER AND REPRODUCTIVE HARM www.P65Warnings.CA.GOV

Gauge	Stranding	Outer Diameter	Auveco No.					
			Black	Brown	Green	Red	White	Yellow
20	7 x 28	0.096	22730	22731	22732	22733	22734	22735
18	16 x 30	0.108	22736		22737	22738	22739	
16	19 x 29	0.121	22740		22741	22742	22743	
14	19 x 27	0.139	22744		22745	22746	22747	
12	19 x 25	0.164	22748		22749	22750	22751	
10	19 x 23	0.196	22752		22753	22754	22755	

PRIMARY WIRE



- Standard PVC Insulation (SE/GPT Type)
- Suitable for most automotive applications.
- Free of stripping, abrasion resistant
- Meets most O.E.M. vehicle standards
- Temperature: Rated -40°C (-40°F) to 105°C (221°F)
- Specifications: SAE J1128, SAE J378

Unit Package: 1 Spool (100 Foot Spool)

CALIFORNIA PROPOSITION 65  **Warning:** CANCER AND REPRODUCTIVE HARM www.P65Warnings.CA.GOV

Gauge	Stranding	Outer Diameter	Auveco No.						
			Black	Blue	Brown	Green	Red	White	Yellow
20	10 x 30	0.085	21341	21342	21345	21343	21339	21340	21344
18	16 x 30	0.092	12425	12426	15256	12427	12423	12424	12428
16	19 x 29	0.104	12431	12432	15257	12433	12429	12430	12434
14	19 x 27	0.117	12437	22725	15258	12439	12435	12436	12440
12	19 x 25	0.142	12443	12444	22726	15259	12441	12442	15260
10	19 x 23	0.175	12447	12448	22729	22728	12445	22727	15263